Service Schedule

Inspection (Main - To be carried out a minimum of every 12 months)	500 Miles (Within 6 Months)	2,000 Miles	4,000 Miles (Main)	6,000 Miles	8,000 Miles (Main)	10,000 Miles	12,000 Miles (Main)	Every 2,000 Thereafter (Main)	Setting
General Bolt/Screw/Nut Check	✓	✓	✓	✓	✓	✓	✓	✓	
Brake System & Hose Wear	✓		✓		✓		✓	✓	
Front & Rear Brake Pad & Disc Wear	✓	✓	✓	✓	✓	✓	✓	✓	
Front & Rear Calliper Brackets	✓		✓		✓		✓	✓	Fr & Rr 26 N⋅m
Front & Rear Brake Disc Bolts	✓		✓		✓		✓	✓	Fr & Rr 42 N⋅m
Tyre Pressure & Wear	√	✓	✓	✓	✓	✓	✓	√	Fr: 25psi, Rr: 29psi or 33psi (With Pillion)
Front & Rear Wheel Spindle	✓		✓		✓		✓	✓	Fr & Rr 59 N⋅m
Bearings (Wheels, Suspension/Swingarm)	✓	✓	✓	✓	✓	✓	✓	✓	
Steering Column	✓	✓	✓	✓	✓	✓	✓	✓	60 N·m
Front & Rear Suspension	✓		✓		✓		✓	✓	Fr 44 / Rr 54 N·m
Swingarm Spindle	✓		✓		✓		✓	✓	54 N·m
Motor & Motor Retainer Nuts	✓		✓		✓		✓	✓	120 N·m
Battery	✓	✓	✓	✓	✓	✓	✓	✓	
Light function	✓	✓	✓	✓	✓	✓	✓	✓	
Electrical System (Test Lights, Horn Etc.)	✓	✓	✓	✓	✓	✓	✓	✓	
Side Stand Switch	✓	✓	✓	✓	✓	✓	✓	✓	





