Service Schedule

Inspection (Main - To be carried out a minimum of every 12 months)	500 Miles (Within 6 Months)	2,000 Miles	4,000 Miles (Main)	6,000 Miles	8,000 Miles (Main)	10,000 Miles	12,000 Miles (Main)	Every 2,000 Thereafter (Main)	Setting (Alloy)	Setting (Spoked)
General Bolt/Screw/Nut Check	✓	✓	✓	✓	✓	✓	✓	✓		
Brake System & Hose Wear	✓		✓		✓		✓	✓		
Front & Rear Brake Pad & Disc Wear	✓	✓	✓	✓	✓	✓	✓	✓		
Front & Rear Calliper Brackets	✓		✓		✓		✓	✓	Fr & Rr 26 N⋅m	
Front & Rear Brake Disc Bolts	✓		✓		✓		✓	✓	Fr & Rr 42 N·m	
Tyre Pressure & Wear	√	✓	~	1	√	√	✓	~	Fr: 25psi, Rr: 29psi or 33psi (With Pillion)	Fr: 29psi, Rr: 33psi or 36psi (With Pillion)
Front & Rear Wheel Spindle	✓		✓		✓		✓	✓	Fr 59/ Rr 88 N·m	
Bearings (Wheels, Suspension/Swingarm)										
Steering Column	✓		✓		✓		✓	✓	74 N·m	
Front & Rear Suspension	✓		✓		✓		✓	✓	Fr 22 (Top Bridge) 32 Bottom Bridge) / Rr 45 N·m	
Swingarm Spindle	✓		✓		✓		✓	✓	59 N·m	
Motor & Motor Retainer Nuts	✓		✓		✓		✓	✓	120 N⋅m	
Drive Belt & Gears	✓		✓		✓		✓	✓		
Battery	✓	✓	✓	✓	✓	✓	✓	✓		
Light function	✓	✓	✓	✓	✓	✓	✓	✓		
Electrical System (Test Lights, Horn Etc.)	✓	✓	✓	✓	✓	✓	✓	✓		
Side Stand Switch	✓	✓	✓	✓	✓	✓	✓	✓		





